

规格说明书 SPECIFICATION				(AT Ta= 25 Degree.)
项目/ITEMS	单位/UNIT	参数/PARAMETERS	备注/NOTES	
尺寸/Dimension	mm	120*120*25	Length* Width *Thickness	
外框/Fan Frame	----	BLACK PBT (UL94V-0)	Glass Fiber Reinforced	
扇叶/Fan Impeller	----	BLACK PBT (UL94V-0)	7 Blades	
轴承种类/Bearing System	<input checked="" type="checkbox"/> S:Sleeve Bearing <input type="checkbox"/> S:Hypro Bearing <input type="checkbox"/> C:CycleSeal Bearing <input type="checkbox"/> B: Dual Ball Bearing			
额定电压/Rated Voltage	VDC	12.0	N/A	
工作电压范围 Operating Voltage Range	VDC	10.8-13.2	N/A	
起动电压/Start-up Voltage	VDC	7.0	N/A	
额定电流/Rated Current	Amp	0.47(MAX:0.56)	At 25°C/Relative Humidity 65%	
标签电流/Label Current	Amp	0.73	At rated Voltage, Measured after 3Mins.	
额定功率/Rated Power	Watt	5.64(MAX:6.72)	At 25°C/Relative Humidity 65%	
额定转速/Rated Speed	RPM	3000±10%	At rated Voltage, Measured after 3Mins	
风量/Air Flow	CFM	104.45(MIN:94.01)	Maximum In Free Air, Refer to 4.2.	
风压/Air Pressure	mmAq	7.34(MIN:5.95)	Maximum When Air Flow = 0	
噪音/Noise Level	dBA	45.9(MAX:48.9)	At Rated Speed, Refer to 4.3.	
马达保护/Motor Protection	Polarity Protection	Yes	Refer to 8.1.	
锁机保护/Locked Motor Protection	Auto Restart	Yes	Refer to 8.2.	
缓启动/Soft Start	----	Yes	N/A	
速度感应/FG Sensor	Tachometer Sensor	Yes	Refer to 2.1.	
锁机报警/RD Alarm	Locked Motor Alarm	No	Refer to 2.1.	
调速控制/PWM Control	----	No	Refer to 2.2.	
防水等级/Waterproof Class	<input type="checkbox"/> IP44 泡油	Motor or PCBa Coating by Insulating Paint		
	<input type="checkbox"/> IP55	Motor NT Vacuum Coating or PCBa Coating by Waterproof Glue		
	<input type="checkbox"/> IP56以上	Motor Coating by Epoxy Waterproof Glue or Injection by Mould		
环保要求/Conform to RoHS	----	Yes	Refer to 6.	
安规规格/Safety Approval	----	<input type="checkbox"/> UL <input type="checkbox"/> CUL <input type="checkbox"/> CE <input type="checkbox"/> TUV		
导线/Lead Wire	UL1007/24AWGx300mm	<input checked="" type="checkbox"/> Red(+) <input checked="" type="checkbox"/> Black(-) <input checked="" type="checkbox"/> White(FG) <input type="checkbox"/> Blue(PWM) <input type="checkbox"/> Yellow(FG)		
端子/Connector	----	2510/3P 正向 黑红白 OR Equivalent	Pin1:-, Pin2:+, Pin3:FG	
套管/Tube	----	No	N/A	
预估寿命/Life Expectancy	小时/Hours	30000	Refer to 7.	
净重/Net Weight	克/Gram	150.7	N/A	
装箱/Packing	件/箱/Pieces/Carton	40	N/A	