

FAN6015-12-101

规格说明书 SPECIFICATION				(AT Ta= 25 Degree.)
项目/ITEMS	单位/UNIT	参数/PARAMETERS	备注/NOTES	
尺寸/Dimension	mm	60*60*15	Length* Width *Thickness	
外框/Fan Frame	-----	BLACK PBT (UL94V-0)	Glass Fiber Reinforced	
扇叶/Fan Impeller	-----	BLACK PBT (UL94V-0)	9 Blades	
轴承种类/Bearing System	<input type="checkbox"/> S:Sleeve Bearing <input type="checkbox"/> S:Hypro Bearing <input checked="" type="checkbox"/> C:CycleSeal Bearing <input type="checkbox"/> B: Dual Ball Bearing			
额定电压/Rated Voltage	VDC	12.0	N/A	
工作电压范围 Operating Voltage Range	VDC	10.8-13.2	N/A	
起动电压/Start-up Voltage	VDC	7.0	N/A	
额定电流/Rated Current	Amp	0.11(MAX:0.17)	At 25°C/Relative Humidity 65% At rated Voltage,Measured after 3Mins.	
标签电流/Label Current	Amp	0.18	N/A	
额定功率/Rated Power	Watt	1.32(MAX:2.04)	At 25°C/Relative Humidity 65% At rated Voltage,Measured after 3Mins	
额定转速/Rated Speed	RPM	4000±600	At 25°C/Relative Humidity 65% At rated Voltage,Measured after 3Mins	
风量/Air Flow	CFM	17.61(MIN:14.97)	Maximum In Free Air,Refer to 4.2.	
风压/Air Pressure	mmAq	3.14(MIN:2.27)	Maximum When Air Flow = 0	
噪音/Noise Level	dBA	30.7(MAX:33.7)	At Rated Speed,Refer to 4.3.	
马达保护/Motor Protection	Polarity Protection	Yes	Refer to 8.1.	
锁机保护/Locked Motor Protection	Auto Restart	Yes	Refer to 8.2.	
缓启动/Soft Start	-----	No	N/A	
速度感应/FG Sensor	Tachometer Sensor	Yes	Refer to 2.1.	
锁机报警/RD Alarm	Locked Motor Alarm	No	Refer to 2.1.	
调速控制/PWM Control	-----	No	Refer to 2.2.	
防水等级/Waterproof Class	<input type="checkbox"/> IP44 or less	马达三防漆包漆 Motor Coating by Insulating Paint		
	<input type="checkbox"/> IP55/56	纳米真空镀膜 Motor process by NT vacuum coating		
	<input type="checkbox"/> IP67/68	灌胶密封 Motor sealed coating by waterproof Glue		
环保要求/Conform to RoHS	-----	Yes	Refer to 6.	
安规规格/Safety Approval	-----	<input type="checkbox"/> UL <input type="checkbox"/> CUL <input type="checkbox"/> CE <input type="checkbox"/> TUV		
导线/Lead Wire	UL 1007/26AWGx300mm	<input checked="" type="checkbox"/> Red(+) <input checked="" type="checkbox"/> Black(-) <input type="checkbox"/> Yellow(FG) <input checked="" type="checkbox"/> White(FG) <input type="checkbox"/> Blue(PWM)		
端子/Connector	-----	2510/3P 正向 黑红白 OR Equivalent	Pin1:-,Pin2:+,Pin3:FG	
套管/Tube	-----	No	N/A	
预估寿命/Life Expectancy	小时/Hours	40000	Refer to 7.	
净重/Net Weight	克/Gram	39.53	N/A	
装箱/Packing	件/箱/Pieces/Carton	100	N/A	