

Blackhawk Trucker Edge Compact Lite

698 - 2100 MHz, 5dBi (ANT-BH-00030)

This premium grade antenna will satisfy 3G and 4G capabilities for all the major networks in Australia and can be used for commercial and industrial 3G and 4G applications. The Blackhawk Omni Trucker Edge Compact LITE at 60cm will provide the perfect solution for voice and data applications. It is lighter in weight than its sister antenna the Trucker Edge Compact, weighing only 1.2kg. The new design includes a smaller barrel which helps reduce weight and minimises vibration and subsequent damaged caused by driving on corrugated roads found in remote and harsh environments.

- Streamline in design and light in weight
- SMA-Male connector
- Ruggedized construction for extreme conditions.
- Can be mounted to car bonnet or bulbar

| Electrical Specifications | | |
|---------------------------|-------------------------------|---------------|
| Frequency Range | 698-960 MHz | 1710-2170 MHz |
| Gain | 4 dBi | 5 dBi |
| VSWR | ≤2.0 | ≤2.0 |
| Polarization | Vertical | |
| Horizontal Beamwidth | 360° | |
| Vertical Beamwidth | 48° | 29° |
| Input Impedance | 50 Ω | |
| Max.Power | 50 W | |
| Lightning Protection | DC Ground | |
| Mechanical Specifications | | |
| Connector | SMA-Male with 4.5m Coax Cable | |
| Dimensions | Ø16x600 mm | |
| Weight | 1.2 kg | |
| Reflector Material | Copper | |
| Radome Material | Fiberglass | |
| Antenna Color | Black / White | |
| Operating Temperature | -40°C to +65 °C | |
| Mounting Pole | Ø38-Ø52 mm | |